



Tension ring connection:

Primed when running:

Tension ring connection for 3mm pipe construction, galvanized with U-shaped seal

For execution material 1.4301:

Tension ring connection for 3mm pipe construction, galvanized with U-shaped seal

In the special version with clamping ring made of material 1.4301 for 1mm and 2mm:

clamping ring for 3mm pipe construction with U-shaped seal

Caution!

The clamping ring is pre-assembled in the factory so that the pipe parts remain rotatable for assembly. In the installed final state, this clamping ring connection must be re-tensioned on site!

Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1
 Lengths and angles – DIN ISO 2768-1 – Tolerance class V

* 1 3=powder-coated with NBR, 1 2=powder-coated with EPDM, 3 1=stainless steel with silicone blue

Pipe	Ø 100	Ø 120	Ø 150	Ø 175	Ø 200	Ø 250	Ø	Ø
Article-no.	1110*3350*	1112*3350*	1115*3350*	1117*3350*	1120*3350*	1125*3350*	-	-
Ø d	100	120	150	175	200	250	-	-
A	70	60	80	100	120	140	-	-
B	120	150	175	200	224	300	-	-
S	1,5	1,5	1,5	1,5	1,5	1,5	-	-
α	55°	45°	45°	45°	45°	45°	-	-
Weight in kg	1,50	1,60	2,40	3,00	3,50	4,60	-	-

Denomination:

Adjustable elbows

Date: 03/20

Datasheet-no. 4/5

Rev. 0