



Galvanised and powder-coated in standard range with EPDM (sponge rubber) seal  
Stainless steel with foam silicone seal

Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1  
Lengths and angles – DIN ISO 2768-1 – Tolerance class V

Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1  
Lengths and angles – DIN ISO 2768-1 – Tolerance class V  
\* 1=powder-coated, 2=galvanised, 3= stainless steel  
except stainless steel not available in 3mm thickness

The article number refers to powder-coated version

Mounting length L 8mm shorter at loose-flange connection i.d. >350

Pipe	Ø 200		Ø 224	Ø 250		Ø 280	Ø 300		Ø 315	Ø 350	
Article-no.	1120*195	1320*195	1122*195	1125*195	1325*195	1128*195	1130*195	1330*195	1131*195	1135*195	1335*195
Ø d	200	198	220	250	248	277	300	298	312	350	348
Ø D	215	216	235	265	266	292	315	316	327	365	366
L	486		486	486		486	486		486	486	
S	1,5	3	1,5	1,5	3	1,5	1,5	3	1,5	1,5	3
A	224		224	224		224	350		350	350	
B	350		350	350		350	350		350	350	
Weight in kg	4,7	9,40	5,2	5,85	11,7	6,6	7,00	14,00	7,35	8,40	16,80
Pipe	Ø 400		Ø 450		Ø 500		Ø 560		Ø 630		Ø
Article-no.	1140*195	1340*195	1245*195	1345*195	1250*195	1350*195	1256*195	1356*195	1263*195	1363*195	-
Ø d	399	396	448	446	498	496	558	556	628	626	-
Ø D	414		464		514		574		644		-
L	486		486		486		486		486		-
S	1,5	3	2	3	2	3	2	3	2	3	-
A	350		500		500		500		500		-
B	350		350		350		350		350		-
Weight in kg	9,1	18,20	11,60	17,40	12,80	19,20	14,30	21,45	16,00	24,00	-

Denomination:

**Cleaning pipes**

Date: 02/20

Datasheet-no. 7/2

Rev. 1