



Double turn-head distributors is not allowed to be switched in the product stream

Performance data:

For grainy products with an bulk density of 750kg/m³, an humidity up to max. 15% and an pipe slope not under 45°

Areas of application:

For all bulk goods in free fall, without overpressure or back pressure promoted in the funding system. Other applications on demand.

Technical Data:

The turn-head distributors are housed in closed casings. The cases are projected funnels. Limit switches are led in the terminal box in terminals. Control must be provided by the customer, motor voltage 230/400 volt, 50 hertz

Number of outlets

Ø120	Ø150	Ø175	Ø200	Ø250
*08,10, 12,14,16 **18,20	*08,10,12 **14,16, 18,20	*08,10,12, 14,16,18, 20	*08,10,12, 14,16,18, 20	*08,10,12 14,16,18, 20

Pipe	Ø120		Ø150		Ø175	Ø200	Ø250
Articel-no.	52*1245	52**1245	52*1545	15**1245	52*1745	52*2045	52*2545
Ød	118		148		173	198	248
ØA	1600	2280	1600	2280	2280	2280	2280
B	4,0		4,5		5,4	6,3	6,3
C	820	1170	810	1160	1145	1135	1110
E	150		160		170	180	210
ØF	1375	2075	1370	2075	2040	2020	1960
G	345		395		430	475	530
I	990	1690	895	1595	1515	1435	1325
K	160		190		215	240	290
L	2220	2410	2210	2400	2385	2375	2900
kg	345	532	350	540	550	562	577
t/h	12		25		45	65	100

Denomination:

Double turn-head distributors 45°

Date: 05/20

Datasheet-no. 10/3

Rev. 0