



Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1  
 Lengths and angles – DIN ISO 2768-1 – Tolerance class V  
 \* 1=powder-coated, 2=galvanised, 3=stainless steel

Pipe	Ø 60-50	Ø 60	Ø 80	Ø 100	Ø 120	Ø 140	Ø 150	Ø 160
Article-no.	1106*4990	1106*499	1108*499	1110*499	1112*499	1114*499	1115*499	1116*499
Ø d	57	57	78	100	120	136	150	159
Ø D	72	72	92	114   115	134	150	164   165	172
Ø B	50	60	78	95   98	122	138	145   148	161
Ø C	51	61	80	100	125	140	150	163
F	10	15	15	15	15	15	20	20
L	80	80	88	100	100	100	100	100
S	1,50	1,50	1	1   1,5	1	1	1   1,5	1
Weight in kg	0,2	0,2	0,2	0,25   0,38	0,3	0,35	0,4   0,5	0,42
Pipe	Ø 175	Ø 200	Ø 224	Ø 250	Ø 280	Ø 300	Ø 315	-
Article-no.	1117*499	1120*499	1122*499	1125*499	1128*499	1130*499	1131*499	-
Ø d	175	200	220	250	280	300	315	-
Ø D	189	214	234	264	294	314	329	-
Ø B	177	198	222	248	276	298	311	-
Ø C	180	200	225	250	278	300	313	-
F	20	20	20	20	20	20	20	-
L	100	100	100	100	100	100	100	-
S	1,00	1,00	1	1	1	1	1	-
Weight in kg	0,45	0,5	0,57	0,65	0,76	0,84	0,86	-

Denomination:

**Hose connections**

Date: 06/24

Datasheet-no. 6/12

Rev. 0