



**Installation position**

Only mount in the drawn installation position.  
 Other installation positions only after consultation.

**Application area**

For all dry products wherever barriers under silos and trough chain conveyors are to be made.  
 At the Silo outlet slide gates is the maximum inlet area < 900cm<sup>2</sup>.  
 Consultation for larger inlets.  
 Not suitable as a gate valve for pressure delivery

\* 0=without spout, 2=spout  
 Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1  
 Lengths and angles – DIN ISO 2768-1 – Tolerance class V

Pipe	Redler outlet slide gates			Silo outlet slide gates		
	Ø 200	Ø 250	Ø 300	Ø 150	Ø 200	Ø 250
Articel-no.	571*2005	571*2505	571*3005	576*1505	576*2005	576*2505
Ø d	199	249	299	149	199	249
A	200	250	300	200	250	300
B	600	600	600	200	250	300
C	710	710	710	304	354	404
E	86	86	86	71	71	71
F	845	995	1145	932	1082	1232
L	360	320	270	150	150	150
S	2	2	2	2	2	2
weight in kg	88,00	91,00	103,00	54,00	64,00	54,00

Denomination:

**Outlet slide gates**  
 electrically-operated

Date: 05/20

Datasheet-no. 8/19

Rev. 0