



**Installation position:**

Only mount in the drawn installation position.  
 Other installation positions after consultation.

**Drive data:**

see diagram-no. TM/S

**Areas of application:**

For dry products wherever a pipe should be shut off in free fall.  
 Not suitable as a gate valve for pressure delivery or delivery with back pressure.

\* 5=powder-coated 6=stainless steel

Pipe	Ø 100	Ø 120	Ø 150	Ø 175	Ø 200	Ø 250	Ø 300
Articel-no.	*6221001	*6221201	*6021502	*6021702	*6022002	*6022502	*6023002
Ø d	99	119	149	174	199	249	299
B	165	185	225	250	295	350	400
C	372	415	505	555	645	780	880
E	80	90	110	123	148	173	198
F	650	692	782	882	1055	1210	1360
L	104	138	152	212	182	217	277
S	2	2	2	2	2	2	2
weight in kg	5,90	6,90	9,20	11,00	19,90	22,20	28,40

In case of placing your order please state the desired signal-current.  
 Please take notice of the following no.-code.  
 The 2-digit number has to be added to 8-digit article-no. code.

Make	Signal-current
.....21 Festo cylinder	230V, AC
.....23 Festo cylinder	24V, AC/DC

Denomination:

**Pipe slide gates**  
 pneumatically operated

Date: 04/20

Datasheet-no.	Rev.
8/17	0