



Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1
 Lengths and angles – DIN ISO 2768-1 – Tolerance class V

- Special lengths and other
 spigots on request

* 1=powder-coated, 2=galvanised, 3= stainless steel

1 Spigots with G (BSP) internal thread
 Thread = BSPP

| Ø Pipe | Ø 60 | Ø 80 | Ø 100 | Ø 120 | Ø 140 | Ø 150 | Ø 160 | h |
|------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|----|
| Ød | 57 | 76 | 99 | 119 | 136 | 149 | 159 | |
| Spigot G= 1/2" | 1106*0400901 | 1208*0400901 | 1210*0400901 | 1212*0400901 | 1214*0400901 | 1215*0400901 | 1216*0400901 | 34 |
| Spigot G= 1" | 1106*0400902 | 1208*0400902 | 1210*0400902 | 1212*0400902 | 1214*0400902 | 1215*0400902 | 1216*0400902 | 43 |
| Spigot G= 1 1/2" | - | 1208*0400903 | 1210*0400903 | 1212*0400903 | 1214*0400903 | 1215*0400903 | 1216*0400903 | 48 |
| Ø Pipe | Ø 175 | Ø 200 | Ø 224 | Ø 250 | Ø 280 | Ø 300 | Ø | h |
| Ød | 174 | 199 | 220 | 249 | 276 | 299 | - | |
| Spigot G= 1/2" | 1217*0400901 | 1220*0400901 | 1222*0400901 | 1225*0400901 | 1228*0400901 | 1230*0400901 | - | 34 |
| Spigot G= 1" | 1217*0400902 | 1220*0400902 | 1222*0400902 | 1225*0400902 | 1228*0400902 | 1230*0400902 | - | 43 |
| Spigot G= 1 1/2" | 1217*0400903 | 1220*0400903 | 1222*0400903 | 1225*0400903 | 1228*0400903 | 1230*0400903 | - | 48 |

Denomination:

Pipe with spigot

Date: 07/24

Datasheet-no.
 3/10

Rev.