



Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1
Lengths and angles – DIN ISO 2768-1 – Tolerance class V
*1=powder-coated, 2=galvanized, 3=chromium-nickel steel

| Pipe | Ø 80 | | Ø 100 | | Ø 120 | | Ø 140 | | Ø 150 | |
|--------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Articel-no. | 1108*260 | - | 1110*260 | 1210*260 | 1112*260 | 1212*260 | 1114*260 | 1214*260 | 1115*260 | 1315*260 |
| Ø d | 77 | - | 100 | 99 | 120 | 118 | 136 | 135 | 150 | 148 |
| Ø D | 92 | - | 115 | 114 | 135 | 136 | 151 | 150 | 165 | 166 |
| A | 40 | | 60 | | 75 | | 75 | | 75 | |
| L | 80 | | 100 | | 110 | | 120 | | 125 | |
| S | 1,5 | - | 1,5 | 2 | 1,5 | 3 | 1,5 | 2 | 1,5 | 3 |
| Weight in kg | 0,55 | - | 0,85 | 1,70 | 1,10 | 2,20 | 1,30 | 2,40 | 1,45 | 2,90 |
| Pipe | Ø 160 | | Ø 175 | | Ø 200 | | Ø 224 | | Ø 250 | |
| Articel-no. | 1116*260 | 1216*260 | 1117*260 | 1317*260 | 1120*260 | 1320*260 | 1122*260 | - | 1125*260 | 1325*260 |
| Ø d | 159 | 159 | 175 | 173 | 200 | 198 | 220 | - | 250 | 248 |
| Ø D | 174 | 174 | 190 | 191 | 215 | 216 | 235 | - | 265 | 266 |
| A | 75 | | 75 | | 90 | | 100 | | 100 | |
| L | 130 | | 140 | | 170 | | 190 | | 200 | |
| S | 1,5 | 2 | 1,5 | 3 | 1,5 | 3 | 1,5 | - | 1,5 | 3 |
| Weight in kg | 1,60 | 2,10 | 1,75 | 3,50 | 2,50 | 5,00 | 3,00 | - | 3,50 | 6,90 |
| Pipe | Ø 280 | | Ø 300 | | Ø 315 | | Ø 350 | | Ø 400 | |
| Articel-no. | 1128*260 | - | 1130*260 | 1330*260 | 1131*260 | 1231*260 | 1135*260 | 1235*260 | 1140*260 | 1240*260 |
| Ø d | 277 | - | 300 | 298 | 312 | 311 | 350 | 349 | 399 | 398 |
| Ø D | 292 | - | 315 | 316 | 327 | 326 | 365 | 364 | 414 | 413 |
| A | 100 | | 120 | | 150 | | 120 | | 150 | |
| L | 220 | | 220 | | 230 | | 250 | | 270 | |
| S | 1,5 | - | 1,5 | 3 | 1,5 | 2 | 1,5 | 2 | 1,5 | 2 |
| Weight in kg | 4,10 | - | 4,50 | 9,00 | 5,20 | 5,40 | 5,65 | 6,20 | 7,00 | 7,80 |
| Pipe | Ø 450 | | Ø 500 | | Ø 560 | | Ø 630 | | Ø | |
| Articel-no. | 1145*260 | 1245*260 | 1150*260 | 1250*260 | - | - | - | - | - | - |
| Ø d | 449 | 448 | 499 | 498 | - | - | - | - | - | - |
| Ø D | 464 | 463 | 514 | 513 | - | - | - | - | - | - |
| A | 150 | | 175 | | - | | - | | - | |
| L | 300 | | 325 | | - | | - | | - | |
| S | 1,5 | 2 | 1,5 | 2 | - | - | - | - | - | - |
| Weight in kg | 8,45 | 9,65 | 10,20 | 11 | - | - | - | - | - | - |

Denomination:

Symmetrical forks 90°

Date: 06/24

Datasheet-no. 1/1

Rev. 1