



\* 5=powder-coated, 6=stainless steel

Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1  
Lengths and angles – DIN ISO 2768-1 – Tolerance class V

Pipe	Ø 80	Ø 100	Ø 120	Ø 140	Ø 150	Ø 160	Ø 175	Ø 200
Article-no.	*7720803	*7721003	*7721203	*7721403	*7721503	*7721603	*7721703	*7722003
Ø d	76	99	119	135	149	159	174	199
A	303	315	325	333	340	347	352	385
B	87	99	109	117	124	123	136	149
C	79	79	79	79	79	79	84	84
L	100	100	120	140	150	160	175	200
S	2	2	2	2	2	2	2	2
Weight in kg	3,60	3,90	4,30	4,70	5,00	5,30	6,60	7,4
Pipe	Ø 224	Ø 250	Ø 280	Ø 300	Ø 315	Ø 350	Ø 400	Ø
Article-no.	*7722203	*7722503	*7722803	*7723003	*7723103	*7723503	*7724003	-
Ø d	219	249	276	299	311	349	399	-
A	395	410	413	439	455	474	499	-
B	159	174	188	199	220	239	264	-
C	84	84	84	84	84	84	84	-
L	200	200	200	200	200	200	200	-
S	2	2	2	2	2	2	2	-
Weight in kg	7,90	8,60	9,60	9,80	14,10	18,20	20,70	-

In case of placing your order please state the desired signal-current.  
Please take notice of the following no.-code.  
The 2-digit number has to be added to 8-digit article-no. code.

Make	Signal-current
.....44 AIR TORQUE Adjustable drive	230V, AC
.....45 AIR TORQUE Adjustable drive	24V, AC/DC

Denomination:

**Throttle valves with seal  
with pneumatic rotary actuator**

Date: 07/24

Datasheet-no. 8/7

Rev. 1