



Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1
Lengths and angles – DIN ISO 2768-1 – Tolerance class V

* 5=powder-coated, 6=stainless steel

Pipe	Ø 60	Ø 80	Ø 100	Ø 120	Ø 140	Ø 150	Ø 160	Ø 175
Article-no.	*6620603	*6620803	*6621003	*8521203	*8521403	*8521503	*8521603	*8521703
Ø d	57	77	100	120	136	150	159	175
A	280	303	315	325	333	340	345	352
B	63	87	99	109	117	124	123	136
C	79	79	79	79	79	79	79	84
L	60	100	100	120	140	150	160	175
S	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5
Weight in kg	3,30	3,60	3,90	4,30	4,70	5,00	5,30	6,60
Pipe	Ø 200	Ø 224	Ø 250	Ø 280	Ø 300	Ø 315	Ø 350	Ø 400
Article-no.	*8522003	*8522203	*8522503	*8522803	*8523003	*8523103	*8523503	*8524003
Ø d	200	220	250	277	300	312	350	399
A	364	374	388	403	414	422	460	485
B	149	159	174	188	199	205	224	248
C	84	84	84	84	84	84	84	84
L	200	200	200	200	200	200	200	200
S	1,5	1,5	1,5	1,5	1,5	2	2	2
Weight in kg	7,40	7,90	8,60	9,10	9,80	10,20	10,90	12,30

In case of placing your order please state the desired signal-current.
Please take notice of the following no.-code.
The 2-digit number has to be added to 8-digit article-no. code.

Make	Signal-current
.....44 AIR TORQUE Adjustable drive	230V, AC
.....45 AIR TORQUE Adjustable drive	24V, AC/DC

Denomination:

**Throttle valves
with pneumatic rotary actuator**

Date: 04/20

Datasheet-no. 8/2

Rev. 1